

FOR APPROVAL:	12/28/2020
REVISION 1:	01/21/2021
REVISION 2:	06/29/2021
REVISION 3:	11/11/2021

WIND SPD,Vult = 161 MPH
RISK CATEGORY = II
EXPOSURE CATEGORY = C
OCCUPANCY CATEGORY = RESIDENTIAL
NET UPLIFTS DEAD LOADS = 9.2 PSF

DESIGN CRITERIA
FBC 2020
TPI 2014


All wood beams are assumed to be drop or headers U.N.O..
Steel beams supplied by others.
FBBO = Flush Beam By Others
DBBO = Drop Beam By Others
SBBO = Steel Beam By Others

N1 : 2x top chord side scab by others, see truss design drawings for details.
N2 : Conv. frame overhang by others.



UNIVERSAL
TIMBER
STRUCTURES

623 West Bridgers Ave,
Auburndale, Florida 33823
(863) 965-0213 Telephone
(866) 688-7526 Toll Free
(863) 967-1082 Fax



TYPICAL JACK TRUSS NAILING:
(2)-0.131"x3.25" NAILS TOE-NAIL @TOP & BOTTOM CONNECTIONS

TYPICAL MONO TRUSS NAILING:
(3)-0.131"x3.25" NAILS TOE-NAIL @TOP & BOTTOM CONNECTIONS

TYPICAL CORNER GIRDER NAILING:
@ OPEN CORNER GIRDER ADD (3)-0.131"x3.25" NAILS TOE-NAIL @TOP & BOTTOM CONNECTIONS;
@ CLOSED CORNER GIRDER ADD (10)-0.131"x 3.25" NAILS TOE-NAIL ALONG END VERTICAL OF CORNER GIRDER INTO HIP GIRDER;

Simpson Summary	
Simpson Type	Qty
HGUS28-2	1
HUS26	15
LUS26	20
THGQH3-SDS4.5	1

Scale: 1/4"=1'-0"

Truss Design Reaction
AG18
- / -2459 lb
Horizontal: - / - lb

DESIGNER	TONY
SCALE	1/4"=1'-0"
JOB #	<i>J20-0109R</i>
MBA #	P20-0464R
SHEET	1 of 2

Truss placement plan and truss designs are based on architectural plans issued 10/20/21.
and structure plans issued 10/20/21

ROOF LOADING	FLOOR LOADING
TCLL = 20 PSF	TCLL = 40 PSF
TCDL = 20 PSF	TCDL = 10 PSF
BCLL = 0 PSF	BCLL = 0 PSF
BCDL = 10 PSF	BCDL = 10 PSF
TOTAL = 50 PSF	TOTAL = 60 PSF
DUR. = 1.25	DUR. = 1.0

Truss member design & connector plates are designed for ASCE 7-16 and maximum forces from both components and claddings and main wind force resisting systems. These trusses have been reviewed to carry an additional 10 psf. non-concurrent bottom chord live load.

N1 : 2x top chord side scab by others, see truss design drawings for details.


N2 : Conv. frame overhang by others.




UNIVERSAL
TIMBER
STRUCTURES

623 West Bridgers Ave,
Auburndale, Florida 33823
(863) 965-0213 Telephone
(866) 688-7526 Toll Free
(863) 967-1082 Fax

Customer: Idyll Const	
Project: Sanchez Res	
Location: 1277 Rainbow Court	
City: Naples, Florida	
DESIGNER	TONY
SCALE	1/2"=1'-0"
JOB #	<i>J20-0109R</i>
MBA #	P20-0464R
SHEET	2 of 2



Truss placement plan and truss designs are based on architectural plans issued 10/20/21.
and structure plans issued 10/20/21



TYPICAL JACK TRUSS NAILING:
(2)-0.131"x3.25" NAILS TOE-NAIL @TOP & BOTTOM CONNECTIONS

TYPICAL MONO TRUSS NAILING:
(3)-0.131"x3.25" NAILS TOE-NAIL @TOP & BOTTOM CONNECTIONS

TYPICAL CORNER GIRDER NAILING:
@ OPEN CORNER GIRDER ADD (3)-0.131"x3.25" NAILS TOE-NAIL @TOP & BOTTOM CONNECTIONS;
@ CLOSED CORNER GIRDER ADD (10)-0.131"x 3.25" NAILS TOE-NAIL ALONG END VERTICAL OF CORNER GIRDER INTO HIP GIRDER;

Hatch Legend	
	40'-2" BEARING
	30'-8" BEARING
	23'-4" BEARING